

Coaxial Panel Connector 23_N-50-0-30/133_N

Description

Straight panel receptacle jack, flange mount

Interface standards

IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

| | |
|--------------------------|--------|
| Impedance | 50 Ω |
| Interface frequency max. | 11 GHz |

Mechanical Data

| | |
|-------------------|-----------|
| Number of matings | 500 |
| Weight | 0.0146 kg |

Environmental Data

| | |
|--|------------------|
| Operating temperature | -65 °C to 125 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|------------------------|-----------------------|
| Centre contact | Copper Beryllium Alloy | SUCOPRO Plating |
| Outer contact | Brass | SUCOPLATE (R) Plating |
| Body | Brass | SUCOPLATE (R) Plating |
| Insulator | PFA / PTFE | |

Related Documents

| | |
|-------------------|--------------|
| Catalogue drawing | DCA-00010110 |
| Mounting hole | DOU-00008784 |

Ordering Information

| | |
|----------------|---------------------|
| Single package | 23_N-50-0-30/133_NE |
|----------------|---------------------|