

product description

PROFIBUS bus connector, RS 485, Fast Connect, without programming port, 90°

SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s 90° cable outlet, Insulation displacement method FastConnect, without PG socket 15.8x 59x 35.6 mm (BxHxD)



suitability for use

For connecting PROFIBUS stations to the PROFIBUS bus cable

### transfer rate

transfer rate / with PROFIBUS DP 9.6 kbit/s ... 12 Mbit/s

### interfaces

number of electrical connections	
<ul style="list-style-type: none"> <li>for PROFIBUS cables</li> </ul>	2
<ul style="list-style-type: none"> <li>for network components or terminal equipment</li> </ul>	1
type of electrical connection	
<ul style="list-style-type: none"> <li>for PROFIBUS cables</li> </ul>	Integrated insulation displacement terminals for 2-core PB FC installation cables
<ul style="list-style-type: none"> <li>for network components or terminal equipment</li> </ul>	9-pin sub D connector
type of electrical connection / FastConnect	Yes

### mechanical data

design of terminating resistor	Resistor combination integrated and connectable via slide switch
material / of the enclosure	plastic
locking mechanism design	Screwed joint

### design, dimensions and weights

type of cable outlet	90 degree cable outlet
width	15.8 mm
height	59 mm
depth	35.6 mm
net weight	10 g

### ambient conditions

ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	-25 ... +60 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +70 °C

### product features, product functions, product components / general

product feature	
<ul style="list-style-type: none"> <li>silicon-free</li> </ul>	Yes
product component	
<ul style="list-style-type: none"> <li>PG connection socket</li> </ul>	No
<ul style="list-style-type: none"> <li>strain relief</li> </ul>	Yes

### standards, specifications, approvals

certificate of suitability

- RoHS conformity
- UL approval

Yes  
Yes

**last modified:**

1/16/2021 