5-520315-5 - ACTIVE

TRIO-MATE

TE Internal #: 5-520315-5 Connector Assembly, Wire-to-Board, 5 Position, 2.54 mm [.1 in] Centerline, 1 Row, Vertical, Socket, Tray, TRIO-MATE, FFC Connectors

View on TE.com >

Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > FFC Connectors



FFC Connector Product Type: Connector Assembly

Connector System: Wire-to-Board

Number of Positions: 5

Centerline (Pitch): 2.54 mm [.1 in]

Number of Rows: 1

Features

Product Type Features

Connector & Housing TypeReceptacleConnector & Contact Terminates ToPrinted Circuit BoardFFC Connector Product TypeConnector Assembly



Connector System	Wire-to-Board
Insertion Force Type	Low Insertion Force (LIF)
Configuration Features	
Number of Positions	5
Number of Rows	1
PCB Mount Orientation	Vertical
Body Features	
Primary Product Color	Black
Contact Features	
Contact Mating Area Plating Material	Tin
Contact Mating Area Plating Material Finish	Bright
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Type	Socket
Contact Current Rating (Max)	1 A

5-520315-5

Connector Assembly, Wire-to-Board, 5 Position, 2.54 mm [.1 in] Centerline, 1 Row, Vertical, Socket, Tray, TRIO-MATE, FFC Connectors



Termination Features

Termination Post & Tail Length	3.56 mm[.14 in]
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Mating Alignment Type	Polarization
PCB Mount Retention	With
PCB Mount Retention Type	Z Bend
Mating Retention	Without
Mating Alignment	With
Panel Mount Feature	Without
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Thermoplastic
Centerline (Pitch)	2.54 mm[.1 in]
FFC Cable Entry	Vertical
Dimensions	

PCB Thickness (Recommended)

1.57 mm[.062 in]

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	960
Packaging Method	Tray
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold

5-520315-5

Connector Assembly, Wire-to-Board, 5 Position, 2.54 mm [.1 in] Centerline, 1 Row, Vertical, Socket, Tray, TRIO-MATE, FFC Connectors



EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Also in the Series | TRIO-MATE



FFC Connectors(66)

Customers Also Bought



5-520315-5

Connector Assembly, Wire-to-Board, 5 Position, 2.54 mm [.1 in] Centerline, 1 Row, Vertical, Socket, Tray, TRIO-MATE, FFC Connectors







Documents

Product Drawings TRIOMATE ASSY V 5P L=3.556LDFR

English

CAD Files 3D PDF

3D

Customer View Model ENG_CVM_CVM_5-520315-5_S.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5-520315-5_S.3d_igs.zip

English

Customer View Model

```
ENG_CVM_CVM_5-520315-5_S.3d_stp.zip
```

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Trio-Mate Flat Flexible Discrete Circuit .100 Connectors English Application Specification

Japanese

Application Specification

English