

### GENERAL DESCRIPTION

The SGM12033A is a three-pole/three-throw (3P3T) addressable switch, which supports a wide operating frequency from 0.4GHz to 5.8GHz. The device provides low insertion loss and high isolation performance. These specifications make the device appropriate for 2G/3G/4G/5G applications, which need high power processing and high linearity.

The device has the ability to integrate serial control system compatible with RFFE standard. Internal driver and decoder for switch control signals are offered by the controller, which makes it flexible in RF path routing and bands selection.

No external DC blocking capacitors required on the RF paths as long as no external DC voltage is applied, which can save PCB area and cost.

The SGM12033A is available in a Green ULGA-2×2-16AL package.

### APPLICATIONS

- Antenna Swapping
- 5G SRS Applications

### FEATURES

- **Operating Frequency Range: 0.4GHz to 5.8GHz**
- **Low Insertion Loss**
- **Input 0.1dB Compression Point: 38dBm**
- **High Isolation**
- **MIPI RFFE V2.1 Interface Compatible**
- **No External DC Blocking Capacitors Required**
- **Available in a Green ULGA-2×2-16AL Package**

### BLOCK DIAGRAM





Figure 1. SGM12033A Block Diagram

**PACKAGE/ORDERING INFORMATION**

MODEL	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE MARKING	PACKING OPTION
SGM12033A	ULGA-2x2-16AL	-40°C to +85°C	SGM12033AYULR16G/TR	GJN XXXX	Tape and Reel, 3000

**MARKING INFORMATION**

NOTE: XXXX = Date Code, Trace Code and Vendor Code.



Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

**ABSOLUTE MAXIMUM RATINGS**

- Supply Voltage,  $V_{IO}$ .....2.5V
- SDA, SCL and USID Control Voltage.....2.5V
- RF Input Power,  $P_{IN}$ .....38dBm
- Junction Temperature.....+150°C
- Storage Temperature Range.....-55°C to +150°C
- Lead Temperature (Soldering, 10s).....+260°C
- ESD Susceptibility
- HBM.....2000V
- CDM.....2000V

**RECOMMENDED OPERATING CONDITIONS**

- Operating Temperature Range.....-40°C to +85°C
- Operating Frequency Range.....0.4GHz to 5.8GHz
- Supply Voltage,  $V_{IO}$ .....1.65V to 1.95V
- SDA, SCL High Voltage.....(0.8 ×  $V_{IO}$ ) to  $V_{IO}$
- SDA, SCL Low Voltage.....0V to (0.2 ×  $V_{IO}$ )
- USID Control Voltage.....0V to  $V_{IO}$

**OVERSTRESS CAUTION**

Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability. Functional operation of the device at any conditions beyond those indicated in the Recommended Operating Conditions section is not implied.


**ESD SENSITIVITY CAUTION**

This integrated circuit can be damaged if ESD protections are not considered carefully. SGMICRO recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage. ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because even small parametric changes could cause the device not to meet the published specifications.

**DISCLAIMER**

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

**PIN CONFIGURATION**



**PIN DESCRIPTION**

PIN	NAME	FUNCTION
1, 3, 11, 13, 15	GND	Ground.
2	RFIN2	RFIN Port 2.
4	RFIN1	RFIN Port 1.
5	NC	No Connection.
6	VIO	Supply Voltage.
7	SDA	RFFE Data Signal.
8	SCL	RFFE Clock Signal.
9	USID	RFFE USID Select Pin.
10	RFOUT1	RFOUT Port 1.
12	RFOUT2	RFOUT Port 2.
14	RFOUT3	RFOUT Port 3.
16	RFIN3	RFIN Port 3.
Exposed Pad	GND	Ground.

**Register\_0 TRUTH TABLE**

Table 1. Register\_0 Truth Table

State	Mode	Register_0 Bits							
		D7	D6	D5	D4	D3	D2	D1	D0
1	RFIN1 Isolation	x	x	x	x	x	0	0	0
2	RFIN1 to RFOUT1	x	x	x	x	x	0	0	1
3	RFIN1 to RFOUT2	x	x	x	x	x	0	1	0
4	RFIN1 to RFOUT3	x	x	x	x	x	0	1	1
5	RFIN2 Isolation	x	x	0	0	0	x	x	x
6	RFIN2 to RFOUT1	x	x	0	0	1	x	x	x
7	RFIN2 to RFOUT2	x	x	0	1	0	x	x	x
8	RFIN2 to RFOUT3	x	x	0	1	1	x	x	x

**Register\_1 TRUTH TABLE**

Table 2. Register\_1 Truth Table

State	Mode	Register_1 Bits							
		D7	D6	D5	D4	D3	D2	D1	D0
1	RFIN3 Isolation	x	x	x	x	x	0	0	0
2	RFIN3 to RFOUT1	x	x	x	x	x	0	0	1
3	RFIN3 to RFOUT2	x	x	x	x	x	0	1	0
4	RFIN3 to RFOUT3	x	x	x	x	x	0	1	1

NOTE: x = Either 0 or 1.

**ELECTRICAL CHARACTERISTICS**

(T<sub>A</sub> = +25°C, V<sub>IO</sub> = 1.65V to 1.95V, typical values are at V<sub>IO</sub> = 1.8V, V<sub>IH</sub> = 1.8V, V<sub>IL</sub> = 0V, P<sub>IN</sub> = 0dBm, VSWR = 1:1, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
<b>DC Characteristics</b>						
Supply Voltage	V <sub>IO</sub>		1.65	1.8	1.95	V
Supply Current	I <sub>VIO</sub>			100	160	μA
Turn-On Time	t <sub>ON</sub>	50% V <sub>DD</sub> to 90% RF			10	μs
RF Path Switching Time (One on Path to Another)	t <sub>SW</sub>	Switching CMD 50% SCL to 90%/10% RF		0.5	2.2	μs
Wake Up Time	t <sub>WK</sub>	End of low power state 50% SCL to 90% RF			10	μs
VIO Reset Time	t <sub>RST</sub>	V <sub>IO</sub> off to it starts to re-power up	10			μs
<b>RF Characteristics</b>						
Insertion Loss (RFINx to RFOUTx)	IL	f <sub>0</sub> = 0.4GHz to 1.0GHz		0.65	0.90	dB
		f <sub>0</sub> = 1.0GHz to 2.0GHz		0.67	1.00	
		f <sub>0</sub> = 2.0GHz to 2.7GHz		0.72	1.10	
		f <sub>0</sub> = 3.0GHz to 3.8GHz		0.78	1.20	
		f <sub>0</sub> = 4.8GHz to 5.8GHz		1.04	1.60	
Isolation (RFINx to RFOUTx)	ISO	f <sub>0</sub> = 0.4GHz to 1.0GHz	35	49		dB
		f <sub>0</sub> = 1.0GHz to 2.0GHz	30	44		
		f <sub>0</sub> = 2.0GHz to 2.7GHz	26	41		
		f <sub>0</sub> = 3.0GHz to 3.8GHz	20	37		
		f <sub>0</sub> = 4.8GHz to 5.8GHz	17	31		
Input Return Loss (RFINx to RFOUTx)	RL	f <sub>0</sub> = 0.4GHz to 1.0GHz		26		dB
		f <sub>0</sub> = 1.0GHz to 2.0GHz		22		
		f <sub>0</sub> = 2.0GHz to 2.7GHz		21		
		f <sub>0</sub> = 3.0GHz to 3.8GHz		18		
		f <sub>0</sub> = 4.8GHz to 5.8GHz		10		
Input 0.1dB Compression Point (RFINx to RFOUTx)	P <sub>0.1dB</sub>	f <sub>0</sub> = 0.4GHz to 2.7GHz, CW		38		dBm
		f <sub>0</sub> = 3.0GHz to 5.8GHz, CW		36		
2 <sup>nd</sup> Harmonic	2f <sub>0</sub>	f <sub>0</sub> = 900MHz at 35dBm		-51		dBm
3 <sup>rd</sup> Harmonic	3f <sub>0</sub>			-41		dBm
2 <sup>nd</sup> Harmonic	2f <sub>0</sub>	f <sub>0</sub> = 1900MHz at 33dBm		-63		dBm
3 <sup>rd</sup> Harmonic	3f <sub>0</sub>			-59		dBm
2 <sup>nd</sup> Harmonic	2f <sub>0</sub>	f <sub>0</sub> = 950MHz at 25dBm		-72		dBm
3 <sup>rd</sup> Harmonic	3f <sub>0</sub>			-65		dBm

MIPI RFFE READ AND WRITE TIMING




Figure 2. Register Write Command Timing Diagram




Figure 3. Register Read Command Timing Diagram

COMMAND SEQUENCE BIT DEFINITIONS

Type	SSC	Command Frame Bits					Parity Bits	Bus Park Cycle	Extended Operation					
		C[11:8]	C[7]	C[6:5]	C[4]	C[3:0]			Data Frame Bits	Parity Bits	Bus Park Cycle	Data Frame Bits	Parity Bits	Bus Park Cycle
Reg Write	Y	SA[3:0]	0	10	A[4]	A[3:0]	Y	-	D[7:0]	Y	Y	-	-	-
Reg Read	Y	SA[3:0]	0	11	A[4]	A[3:0]	Y	Y	D[7:0]	Y	Y	-	-	-
Reg0 Write	Y	SA[3:0]	1	D[6:5]	D[4]	D[3:0]	Y	Y	-	-	-	-	-	-

Legends:

SSC = Sequence Start Command

SA = Slave Address

A = Register Address

D = Data Bit

**REGISTER MAPS****Register\_0**

Register Address: 0x00; R/W

**Table 3. Register\_0 Register Details**

Bits	Bit Name	Description	Default	Type	B/G	Trig
D[7:0]	MODE_CTRL	See Table 1 section.	00000000	R/W	No	0, 1, 2

**Register\_1**

Register Address: 0x01; R/W

**Table 4. Register\_1 Register Details**

Bits	Bit Name	Description	Default	Type	B/G	Trig
D[7:0]	MODE_CTRL	See Table 2 section.	00000000	R/W	No	0, 1, 2

**RFFE\_STATUS**

Register Address: 0x1A; R/W

**Table 5. RFFE\_STATUS Register Details**

Bits	Bit Name	Description	Default	Type	B/G	Trig
D[7]	SOFTWARE_RESET	0: Normal 1: Software reset During software reset, this register and all configurable registers are set to their default values except for reserved registers.	0	R/W	No	No
D[6]	COMMAND_FRAME_PARITY_ERR	Command frame parity error.	0	R/W	No	No
D[5]	COMMAND_LENGTH_ERR	Command length error.	0	R/W	No	No
D[4]	ADDRESS_FRAME_PARITY_ERR	Address frame parity error.	0	R/W	No	No
D[3]	DATA_FRAME_PARITY_ERR	Data frame parity error.	0	R/W	No	No
D[2]	RD_IVD_ADD	Read command to an invalid address.	0	R/W	No	No
D[1]	WR_IVD_ADD	Write command to an invalid address.	0	R/W	No	No
D[0]	BID_GID_ERR	Read command with a BROADCAST_ID or GSID. When this register is read, it will reset.	0	R/W	No	No

**GROUP\_SID**

Register Address: 0x1B; R and R/W

**Table 6. GROUP\_SID Register Details**

Bits	Bit Name	Description	Default	Type	B/G	Trig
D[7:4]	Reserved	Reserved.	0000	R	No	No
D[3:0]	GSID	Group slave ID.	0000	R/W	No	No

**REGISTER MAPS (continued)****PM\_TRIG**

Register Address: 0x1C; R/W and W

Table 7. PM\_TRIG Register Details

Bits	Bit Name	Description	Default	Type	B/G	Trig
D[7]	PWR_MODE_1	0: Normal 1: Low power	0	R/W	Yes	No
D[6]	PWR_MODE_0	0: Active - Normal 1: Startup - All registers are reset to the default	0	R/W	Yes	No
D[5]	TRIGGER_MASK_2	0: TRIGGER_2 enabled 1: TRIGGER_2 disabled	0	R/W	No	No
D[4]	TRIGGER_MASK_1	0: TRIGGER_1 enabled 1: TRIGGER_1 disabled				
D[3]	TRIGGER_MASK_0	0: TRIGGER_0 enabled 1: TRIGGER_0 disabled				
D[2]	TRIGGER_2	0: Keep its associated destination registers unchanged 1: Load its associated destination registers with the data in the parallel shadow register, provided TRIGGER_MASK_2 is set to logic '0'	0	W	Yes	No
D[1]	TRIGGER_1	0: Keep its associated destination registers unchanged 1: Load its associated destination registers with the data in the parallel shadow register, provided TRIGGER_MASK_1 is set to logic '0'	0	W	Yes	No
D[0]	TRIGGER_0	0: Keep its associated destination registers unchanged 1: Load its associated destination registers with the data in the parallel shadow register, provided TRIGGER_MASK_0 is set to logic '0'	0	W	Yes	No

**PRODUCT\_ID**

Register Address: 0x1D; R

Table 8. PRODUCT\_ID Register Details

Bits	Bit Name	Description	Default	Type	B/G	Trig
D[7:0]	PRODUCT_ID	Product number.	00000100	R	No	No

**MANUFACTURER\_ID**

Register Address: 0x1E; R

Table 9. MANUFACTURER\_ID Register Details

Bits	Bit Name	Description	Default	Type	B/G	Trig
D[7:0]	MANUFACTURER_ID[7:0]	Lower eight bits of Manufacturer ID. Read-only. Note that during USID programming, the write command sequence is executed on the register, but the value does not change.	01001010	R	No	No

**MAN\_USID**

Register Address: 0x1F; R and R/W

Table 10. MAN\_USID Register Details

Bits	Bit Name	Description	Default	Type	B/G	Trig
D[7:4]	MANUFACTURER_ID[11:8]	Upper four bits of Manufacturer ID. Read-only. Note that during USID programming, the write command sequence is executed on the register, but the value does not change.	0000	R	No	No
D[3:0]	USID	USID pin connected to GND.	1010	R/W	No	No
		USID pin connected to VIO.	1011			




**POWER ON AND OFF SEQUENCE**

Once the VIO voltage drops to 0V, the VIO waits at least 10µs before repowering (see Figure 4).


In order to ensure the correct data transmission, SDA/SCL must be sent after VIO has been applied at least 120ns. There must be at least 15µs to apply RF power after VIO has been applied. Wait a minimum of typically 10µs after RFFE bus is idle to apply an RF signal (see Figure 5).

Do not apply RF power during switching. To ensure this, the RF power needs to be removed before the register write operation that changes the switching mode is completed (see Figure 6).


When the low power mode is used, a delay time of 10µs is required to exit the low power mode (see Figure 7).




**Figure 4. Digital Supply Detail**



**Figure 5. Digital Signal/RF Power-On Detail**




**Figure 6. Switch Event Timing**



**Figure 7. Low Power Mode Exit Timing**


**TYPICAL APPLICATION CIRCUIT**



NOTE: \* Matching for optimized RF performance, it may be changed according to different applications.

**Figure 8. SGM12033A Typical Application Circuit**

**EVALUATION BOARD LAYOUT**



**Figure 9. SGM12033A Evaluation Board Layout**

**REVISION HISTORY**

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.


<b>Changes from Original (MAY 2022) to REV.A</b>	<b>Page</b>
Changed from product preview to production data.....	All

---

# PACKAGE INFORMATION

## PACKAGE OUTLINE DIMENSIONS

### ULGA-2x2-16AL



Symbol	Dimensions In Millimeters		
	MIN	MOD	MAX
A	0.510	0.550	0.590
A1	0.170 REF		
A2	0.380 REF		
b	0.150	0.200	0.250
D	1.950	2.000	2.050
E	1.950	2.000	2.050
D1	0.900	1.000	1.100
E1	0.900	1.000	1.100
e	0.400 BSC		
L	0.150	0.200	0.250
k	0.200 TYP		
eee	-	0.080	-

NOTE: This drawing is subject to change without notice.

# PACKAGE INFORMATION

## TAPE AND REEL INFORMATION

### REEL DIMENSIONS



### TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

### KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
ULGA-2×2-16AL	7"	9.5	2.25	2.25	0.75	4.0	4.0	2.0	8.0	Q2

000001

# PACKAGE INFORMATION

## CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

## KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
7" (Option)	368	227	224	8
7"	442	410	224	18

DD0002