



SPECIFICATIONS:

1. ELECTRICAL CHARACTERISTICS:
 - 1-1. CONTACT RESISTANCE: 30mΩ MAX.
 - 1-2. DIELECTRIC WITHSTANDING VOLTAGE: 100V AC FOR ONE MINUTE.
 - 1-3. INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC
2. MECHANICAL CHARACTERISTICS:
 - 2-1. INSERTION FORCE :0.5-2.0KgF(REF.)
 - 2-2. WITHDRAWAL FORCE :0.8-2.0KgF(REF.)
3. LIFE TEST: 10,000 CYCLES.
4. TO CONFORM TO THE KRCDNN HAZARDOUS SUBSTANCE FREE SPEC.

			GENERAL TOLERANCE	制图	深圳市华灿天禄电子有限公司		
			DIM TOL	DRAWING	ShenzhenhuaciantianluELECTRONICS CO.,LTD		
			X.X ±0.30	审核	产品名称	TYPE C F 16P TOP MOUNT (L:7.35) WITH POST	版本
			X.XX ±0.20	CHECK	TITLE	(单排 板上 带柱 四脚插板 橙胶芯)	REV.
1	初版发行		X.XXX ±0.10	批准	产品料号	HC-TYPE-C-16P-01A-0	单位
序号	变更内容	日期	Angle ±3.0°	投影	PART NO.		UNITS
No.	MODIFY CONTENT	MODIFY DATE		Projection	MATERIAL		SHEET
							1/3