

M8

0805 ... 0...

Cordsets M8



Actuator/sensor cordset with overmolded connector

Cable end 1:

M8 female, angled, A-coded, IP67

Cable end 2:

blunt cut

Cable:

PVC, black

Approvals:



M8

0805 ... 0...

-
- [0831 ... T10CP](#)
 - [0831 ... T8CW ...](#)
 - [0832 ...S9 T8CP](#)
 - [6157 8055 S01 4W](#)
 - [6157 8055 S03 8W](#)
 - [6157 8055 S06 16W](#)
 - [6157 8055 S09 24W](#)

- Accessories
- [9908 CPF0](#)
-

M8

0805 ... 0...

Designation	Pole Number	Connected Cable	PU (Pieces)	MDQ (Pieces)	Dimensions L (mm)
0805 04 002 2m	4	PVC, black, 4 x 0.34 mm ² (AWG 22), 910002, UL-style 2464	5	10	2000
0805 04 002 5m	4	PVC, black, 4 x 0.34 mm ² (AWG 22), 910002, UL-style 2464	1	10	5000
0805 04 002 10m	4	PVC, black, 4 x 0.34 mm ² (AWG 22), 910002, UL-style 2464	1	10	10000
0805 06 024 1m	6	PVC, black, 6 x 0.25 mm ² (AWG 24), 910024, UL-style 2464	5	10	1000
0805 06 024 2m	6	PVC, black, 6 x 0.25 mm ² (AWG 24), 910024, UL-style 2464	5	10	2000
0805 06 024 5m	6	PVC, black, 6 x 0.25 mm ² (AWG 24), 910024, UL-style 2464	1	10	5000
0805 08 025 1m	8	PVC, black, 8 x 1.34 mm ² (AWG 26), 910025, UL-style 2464	5	10	1000
0805 08 025 2m	8	PVC, black, 8 x 1.34 mm ² (AWG 26), 910025, UL-style 2464	5	10	2000
0805 08 025 5m	8	PVC, black, 8 x 1.34 mm ² (AWG 26), 910025, UL-style 2464	1	10	5000

Packaging:
in a plastic bag