




REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2025.2.22	阿树




Specifications:
规格:
Voltage rating: 250V AC/DC
额定电压: 250V AC/DC
Current rating: 1A AC/DC
额定电流: 1A AC/DC
Withstanding voltage: 300V AC/minute
耐受电压: 300V AC/分钟
Temperature range: $-40^{\circ}\text{C} - +105^{\circ}\text{C}$
温度范围: $-40^{\circ}\text{C} - +105^{\circ}\text{C}$
Insulation resistance: $\geq 500\text{M}\Omega$
绝缘电阻: $\geq 500\text{M}\Omega$
Contact resistance: $\leq 20\text{m}\Omega$
接触电阻: $\leq 20\text{m}\Omega$
Material: PA6T UL94V-0
材质: PA6T UL94V-0
Plating Category: 1U"Gold
镀层: 1U"Gold
Wave soldering temperature: $255 \pm 5^{\circ}\text{C}$, 10S
波峰焊温度: $255 \pm 5^{\circ}\text{C}$, 10S

PART NO.:

X1321 F V-2xXX-C43 D24
① ② ③ ④ ⑤ ⑥

- ① Series No
- ② Category: F-Female
- ③ Welding Board Angle: V-Straight 180°
- ④ Row No. Pin No: 2xXX-2x01~2x40P
- ⑤ Plastic Height: $C = 4.3\text{mm}$
- ⑥ Pin Length: $D = 2.4\text{mm}$



X1321FV-2xXX-C43D24	PA6T	Brass	X1321W
PART NO	Material	Material(Pin)	Suitable XKB Wafer

AuGLAR	$\pm 5^{\circ}$
X.	± 0.40
X.x	± 0.30
X.xx	± 0.20
X.xxx	± 0.15
UNSPECIFIED TOLERANCES	



DESIGN	阿树	VIEW:		MODEL TYPE:	1.27mm BTB Connector
CHECKED		UNIT:	mm/in	PART NO.:	X1321FV-2xXX-C43D24
APPROVED		SIZE:	A4	DWG NO.:	