



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Interface**

According to

IEC 61169-4, EN 122190, DIN 47223

**Documents**

N/A

**Material and plating**

**Connector parts**

- Center contact
- Outer contact
- Dielectric
- Substrate

**Material**

- Beryllium copper
- Brass
- PPE
- Al<sub>2</sub>O<sub>3</sub>

**Plating**

- Silver, 3-6 µm
- Flash white bronze over silver(e.g. Optargen®)

# Technical Data Sheet

# Rosenberger

7-16

Termination  
Jack 2 Watt

60K15R-002N1

## Electrical data

Impedance	50 $\Omega$
Frequency	DC to 3 GHz
Return loss	$\geq 34.1$ dB, DC to 2 GHz $\geq 26.0$ dB, 2 GHz to 3 GHz
Power handling (at 25 °C, sea level)	$\leq 2$ W, derated linearity by 0.02 W/K

## Mechanical data

Mating cycles	$\geq 500$
Center contact captivation	$\geq 200$ N
Coupling torque (recommended)	25 to 30 Nm
Proof torque	$\leq 35$ Nm

## Environmental data

Temperature range	-40 °C to +85 °C
RoHS	compliant

## Tooling

N/A

## Suitable cables

N/A

## Packing

Standard	1 pce in bag
Weight	85 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Kerstin Herzog	28.07.05	Markus Müller	20.07.18	c00	18-1027	Marion Striegler	20.07.18
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de					Tel. : +49 8684 18-0 Email : info@rosenberger.de		Page 2 / 2