Product availability: Non-Stock - Not normally stocked in distribution facility



#### Main

Commercial Status	Commercialised
Range of product	OsiSense XU
Series name	General purpose
Electronic sensor type	Photo-electric sensor
Sensor name	XUVA
Sensor design	Fork L
Detection system	Thru beam
Emission	Red LED, modulated
Passage width	1.97 in (50 mm)
Passage depth	1.97 in (50 mm)
Material	Metal/Plastic
Supply circuit type	DC
Wiring technique	3-wire
Discrete output type	PNP
Discrete output function	1 NO
Electrical connection	1 male connector M8, 3 pins
Product specific application	Detection on small conveyor
[Sn] nominal sensing distance	1.97 in (50 mm)

### Complementary

Enclosure material	Painted aluminium and polyamide/glass	
Spot diameter	0.05 in (1.2 mm)	
Type of output signal	Discrete	
Output type	Solid state	
Status LED	1 LED (yellow) for output state	
[Us] rated supply voltage	1224 V DC with reverse polarity protection	
Supply voltage limits	1030 V DC	
Switching capacity in mA	100 mA (overload and short-circuit protection)	
Switching frequency	4000 Hz	
Voltage drop	<= 1.5 V (closed state)	
Current consumption	< 20 mA (no-load)	
Product weight	0.180.42 lb(US) (0.080.19 kg)	
Product weight	0.180.42 lb(US) (0.080.19 kg)	

#### Environment

Product certifications	CE
Ambient air temperature for operation	14140 °F (-1060 °C)
Ambient air temperature for storage	-40176 °F (-4080 °C)
Immunity to ambient light	5000 lux with incandescent bulb 10000 lux with natural light
Vibration resistance	7 gn, amplitude = +/- 0.75 mm (f = 1055 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60068-2-27
IP degree of protection	IP67 IP65

## Ordering and shipping details

Category	22481 - SENSORS, PHOTOELECTRIC
Discount Schedule	DS2
GTIN	003389119052351
Nbr. of units in pkg.	1
Package weight(Lbs)	0.22
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	FR

# Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Will be Compliant on 4Q2014

### Contractual warranty

Period	18 months



# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XUVA0505PANM8