



### SPECIFICATIONS

Current Rating: 1.5 Amps  
 Insulation Resistance:  $1000M\ \Omega$  Min  
 Contact Resistance:  $20m\ \Omega$  Max  
 Withstanding Voltage: AC 500V  
 Operation Temperature:  $-40^{\circ}$  to  $+105^{\circ}$   
 Contact Material: Brass  
 Standard: PA6T  
 Insulator Material: Polyester (UL 94V-0)  
 Contact Plating: Gold Flash  
 Max. Processing Temp:  $240^{\circ}$  C for 30-60seconds  
 ( $260^{\circ}$  C for 5 seconds)

**韩下 HANXIA** 深圳市韩下电子有限公司

UNLESS OTHERWISE SPECIFIED TOLERANCE  
 X :  $\pm0.3$  X° :  $\pm5^{\circ}$   
 X.X :  $\pm0.2$  X.X° :  $\pm1^{\circ}$   
 X.XX :  $\pm0.1$  X.XX° :  $\pm0.5^{\circ}$

DRAWN NAME:		HX PM2.0-1x10P ZC			
SIZE	A4	SCALE	N:1	PROJECT NO.	
REV	A	UNIT	mm	PROJECT	
DRAWN		CHECKED:		APPROVED:	
黄彬 2020.6.24		张伟 2020.6.24		罗小春 2020.6.24	

No. of	DIM. A	DIM. B	No. of	DIM. A	DIM. B	No. of	DIM. A	DIM. B	No. of	DIM. A	DIM. B
1	0.00	2.00	11	20.00	22.00	21	40.00	42.00	31	60.00	62.00
2	2.00	4.00	12	22.00	24.00	22	42.00	44.00	32	62.00	64.00
3	4.00	6.00	13	24.00	26.00	23	44.00	46.00	33	64.00	66.00
4	6.00	8.00	14	26.00	28.00	24	46.00	48.00	34	66.00	68.00
5	8.00	10.00	15	28.00	30.00	25	48.00	50.00	35	68.00	70.00
6	10.00	12.00	16	30.00	32.00	26	50.00	52.00	36	70.00	72.00
7	12.00	14.00	17	32.00	34.00	27	52.00	54.00	37	72.00	74.00
8	14.00	16.00	18	34.00	36.00	28	54.00	56.00	38	74.00	76.00
9	16.00	18.00	19	36.00	38.00	29	56.00	58.00	39	76.00	78.00
10	18.00	20.00	20	38.00	40.00	30	58.00	60.00	40	78.00	80.00