



**规格说明: Specifications:**

1. 额定电流: Current Rating  
1.5A/contact terminal
2. 额定电压: Voltage Rating  
30V DC
3. 接触电阻: Contact Resistance  
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:  
500 V AC AT Sea Level
5. 绝缘电阻: Insulation Resistance:  
1000MEGA ohms MIN

**物理性能: Mechanical:**

1. 插拔力: Connector Mate and Unmate Force  
Mate force: 3.57kgf(MAX)  
Unmate force: 1.02kgf(MIN)
2. 端子保持力: Terminal Retention  
1.0kgf(MIN)

1. 塑胶: Housing:  
Hing Temperature Thermoplastics,

2. 端子: Contact: Copper Alloy C2680

3. 外壳: Shell: Copper Alloy C2680/SPCC

1. 端子: Contact: Plated Gold in Mating Area,  
Tin On Solder Talls

端子四周镀50U”(MIN)镍,镀金区域镀100—200U”镀金1U”

铜壳四周镀80U”(MIN)镍  
Nickel Plating

成品图 MANUFACTURE DWG	深圳市金航标电子有限公司		WWW.BDS666.COM	
公差一览表 TOLERANCE UNLESS OTHERWISE	KH-AF180WJ-17.5		0755-83044319	
X±0.15	X.±5°	日期 DATE	单位 UNIT	MM
XX±0.05	.X±2°	审核 CHECKED	比例 SCALE	1 : 1
XXX±0.02	.XX±1°	批准 APPROVE	画法 VIEW	第一角 FIRST ANGLE
			图号 DRAWING	
			设计 DESIGN	
			品名 NAME	插座 RECEPTACLE
			版本 VER	
				页码 SHEET