

# SAC-6P-15,0-970/FS SCO - Bus system cable



1428607

<https://www.phoenixcontact.com/us/products/1428607>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Bus system cable, VARAN (100 Mbps), 6-position, SANTOPRENE halogen-free/TPE halogen-free, black RAL 9005, shielded, free cable end, on Socket straight M12 SPEEDCON, coding: A, cable length: 15 m

## Commercial data

Item number	1428607
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	BF04
Product key	BF1CMM
Catalog page	Page 324 (PC-2011)
GTIN	4046356322881
Weight per piece (including packing)	1,161.1 g
Weight per piece (excluding packing)	1,110 g
Customs tariff number	85444290
Country of origin	PL

# SAC-6P-15,0-970/FS SCO - Bus system cable



1428607

<https://www.phoenixcontact.com/us/products/1428607>

## Technical data

### Product properties

Product type	Data cable preassembled
Application	Standard
Sensor type	VARAN
Number of positions	6
No. of cable outlets	1
Coding	A

### Insulation characteristics

Overvoltage category	II
Degree of pollution	3

### Interfaces

Bus system	VARAN
Signal type/category	VARAN, 100 Mbps

### Signaling

Status display	No
Status display present	No

### Electrical properties

Insulation resistance	≥ 100 MΩ
Nominal voltage $U_N$	30 V AC
	30 V DC
Nominal current $I_N$	2 A
Transmission medium	Copper

### Material specifications

Flammability rating according to UL 94	HB
Seal material	NBR
Material of grip body	TPU, hardly inflammable, self-extinguishing
Contact material	CuZn
Contact surface material	Ni/Au
Contact carrier material	TPU GF
Material for screw connection	Zinc die-cast, nickel-plated

### Connection data

#### Pin assignment

Contact   Color (signal designation)   Contact (optional)	1 (Socket)
	4 (Socket)
	6 (Socket)   BU (Power)
	7 (Socket)   BN (Power)

# SAC-6P-15,0-970/FS SCO - Bus system cable



1428607

<https://www.phoenixcontact.com/us/products/1428607>

	5 (Socket)   GNWH (RD+)
	8 (Socket)   GN (RD-)
	2 (Socket)   OGWH (TD+)
	3 (Socket)   OG (TD-)

## Connector

### Connection 1

Type	free cable end
------	----------------


### Connection 2

Type	free cable end free cable end
------	-------------------------------

## Cable/line

Cable length	15 m
--------------	------

### VARAN [970]

Dimensional drawing	
Cable weight	81 kg/km
Number of positions	6
Shielded	yes
Cable type	VARAN [970]
Conductor structure	1x2xAWG22/19 + 1x4xAWG24/19
Conductor structure signal line	19x 0.13 mm
AWG signal line	24
Conductor cross section	4x 0.25 mm <sup>2</sup> (Signal line) 2x 0.38 mm <sup>2</sup> (Power supply)
Wire diameter incl. insulation	1.35 mm (Signal line) 1.5 mm (Power supply)
External cable diameter	7.80 mm ±0.2 mm
Outer sheath, material	SANTOPRENE halogen-free
External sheath, color	black RAL 9005
Conductor material	Bare Cu litz wires
Material, filler	Yarn
Material wire insulation	PP
Single wire, color	brown, blue, white/orange, white/green, green, orange
Type of pair shielding	Tinned copper braided shield, 95 % covering
Overall twist	1 star quad and 2 wires with 2 fillers

# SAC-6P-15,0-970/FS SCO - Bus system cable



1428607

<https://www.phoenixcontact.com/us/products/1428607>

Max. conductor resistance	77 $\Omega$ /m (Data cable)
Insulation resistance	5 $G\Omega$ *km (Data cable)
Wave impedance	100 $\Omega$ $\pm$ 15 %
Working capacitance	50 nF (Data cable)
Nominal voltage, cable	125 V (Data cable) 48 V (Power supply)
Test voltage	2000 V (Power supply) max. 700 V AC (Data cable)
Smallest bending radius, fixed installation	$\geq$ 93 mm
Smallest bending radius, movable installation	$\geq$ 93 mm
Max. bending cycles	3000000
Bending radius	93 mm
Traversing path	2 m
Traversing rate	1 m/s
Acceleration	2 m/s <sup>2</sup>
Halogen-free	in accordance with DIN EN 50267-2-1
Ambient temperature (operation)	-20 °C ... 80 °C (Cable)
Ambient temperature (installation)	0 °C ... 50 °C

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP65
	IP67


# SAC-6P-15,0-970/FS SCO - Bus system cable

1428607

<https://www.phoenixcontact.com/us/products/1428607>


## Drawings

Schematic diagram



Pin assignment M12 socket, 8-pos., A-coded, view female side

Dimensional drawing



M12 x 1 socket, straight, shielded


# SAC-6P-15,0-970/FS SCO - Bus system cable



1428607

<https://www.phoenixcontact.com/us/products/1428607>

Circuit diagram



# SAC-6P-15,0-970/FS SCO - Bus system cable



1428607

<https://www.phoenixcontact.com/us/products/1428607>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1428607>



**EAC-RoHS**

Approval ID: RU D-DE.HB35.B.00387

# SAC-6P-15,0-970/FS SCO - Bus system cable



1428607

<https://www.phoenixcontact.com/us/products/1428607>

## Classifications

### ECLASS

ECLASS-11.0	27060307
ECLASS-12.0	27060307
ECLASS-13.0	27060307

### ETIM

ETIM 9.0	EC001855
----------	----------

### UNSPSC

UNSPSC 21.0	26121600
-------------	----------



# SAC-6P-15,0-970/FS SCO - Bus system cable



1428607

<https://www.phoenixcontact.com/us/products/1428607>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)