



Search within category GO



PV10-P55-DY

Pin Terminal, 12 10 AWG, vinyl insulated, .55 pin length, bulk package.  
 PV10-P55-DY replaces PV10-P55-D

BUY NOW

DESIGN / INSTALL

Specs	Packaging Details	Tools	Documents
Note	PV10-P55-DY replaces PV10-P55-D		
Pin Length (In.)	0.55		
Pin Length (mm)	14.0		
Wire Range In. (mm <sup>2</sup> )	12 - 10 AWG (4.0 - 6.0)		
Barrel Configuration	Standard		
Barrel Type	Brazed Seam		
Base Material	Copper		
Insulation	Vinyl		
Panduit Color Code	Yellow		
Plating Type	Tin		
Part Number Series	PV		
Length In (mm)	1.1 (27.9)		
Max. Insulation Diameter In. (mm)	0.25 (6.3)		
Stock In. (mm)	0.03 (0.8)		
Width In (mm)	0.1 (2.5)		
Wire Strip Length In. (mm)	5/16 (7.9)		
Flammability Rating	UL94-V0		
Max. Voltage Rating	600V		
Temperature Rating	221 Degrees Fahrenheit (105 Degrees Celsius)		
CA-800/EZ Series Crimp Die	NA		
Tool	CT-100A, CT-260, CT-1550, CT-1551, CT-2300/ST with CD-550, CT-2500/L with CT-2550CH		
CSA Certified	No		
UL Listed	No		
Packaging Type	Box		
Part Features	Solid pin designed to prevent damage to the wire from over tightening, resulting in a reliable electrical connection Insulation support helps to prevent wire damage in bending applications Internal barrel serrations assure good wire contact and maximum tensile strength		
RoHS Compliancy Status	Compliant		
Min. Order Qty.	500		

★ Add to Favorites Add to BOM