



**RESISTANCE VS TEMPERATURE CHARACTERISTICS:**

Temp(°C)	R min (KΩ)	R nom (KΩ)	R max (KΩ)	Temp(°C)	R min (KΩ)	R nom (KΩ)	R max (KΩ)
-40	246.7	257.4	268.5	50	3.816	3.891	3.967
-35	182.8	190.1	197.8	55	3.202	3.270	3.340
-30	136.9	142.0	147.3	60	2.698	2.761	2.825
-25	103.6	107.1	110.8	65	2.284	2.341	2.399
-20	79.090	81.580	84.150	70	1.941	1.993	2.045
-15	60.950	62.700	64.500	75	1.656	1.703	1.751
-10	47.360	48.610	49.870	80	1.419	1.461	1.504
-5	37.100	37.980	38.870	85	1.221	1.259	1.298
0	29.280	29.900	30.530	90	1.054	1.088	1.124
5	23.250	23.680	24.130	95	0.913	0.944	0.977
10	18.590	18.900	19.210	100	0.794	0.822	0.851
15	14.970	15.190	15.400	105	0.692	0.718	0.745
20	12.140	12.280	12.430	110	0.606	0.629	0.653
25	9.900	10.000	10.100	115	0.531	0.552	0.574
30	8.092	8.190	8.288	120	0.467	0.487	0.507
35	6.652	6.746	6.840	125	0.412	0.430	0.448
40	5.499	5.587	5.676	130	0.357	0.373	0.389
45	4.569	4.651	4.734	135	0.302	0.316	0.330

**NOTES:**

1. RESISTANCE @ 25°C : 10KΩ±1%
2. BETA VALUE (0/50°C) : 3600K±1%
3. OPERATING TEMPERATURE RANGE : -40°C TO +135°C.
4. DISSIPATION FACTOR : 1.5mW/°C
5. THERMAL TIME CONSTANT : LESS THAN 3SECONDS IN WATER
- 6.INSULATION RESISTANCE : 10MΩ AT 100 VDC

FUNCTIONAL SYMBOLS ▽/A = 0 ▽/E = 0 ▽/V = 0	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	CURRENT REV DESC:		<b>molex</b>		
	DIMENSION UNITS: mm	SCALE: NTS	EC NO: 657230			
DIVISIONAL SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DRWN: RAVIKM	2021/03/04	PRODUCT CUSTOMER DRAWING	
	ANGULAR TOL ± °	4 PLACES ±	CHK'D: RBBHASKAR	2021/03/05	DOCUMENT NUMBER	
	3 PLACES ±	2 PLACES ±	APPR: RBBHASKAR	2021/03/05	2152703603	DOC TYPE: PSD
	1 PLACE ±	0 PLACES ±	INITIAL REVISION:	DRWN: RAVIKM	2021/03/04	DOC PART: 000
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING: A3-SIZE	SERIES: 215270	MATERIAL NUMBER: 2152703603	CUSTOMER: OTS
						REVISION: A
						SHEET NUMBER: 1 OF 1