

SENCITY Planar WiFi Antenna 1356.19.0009

Description

SENCITY® Spot-S indoor antenna
 Directional, $\pm 45^\circ$ slant dual linear polarised WiFi - Antenna
 WLAN IEEE 802.11 a/h/n
 5.150 GHz - 5.875 GHz
 Wall mounting material included
 For indoor applications



Product Configuration

Technical Data

Electrical Data

Band 1	
Frequency (MHz)	5150 - 5875
VSWR	1.7
Impedance (Ohm)	50
Gain (dBi)	10
3dB beamwidth (h) (°)	60
3dB beamwidth (v) (°)	60
Composite power max (W)	10
Ambient temperature (°C)	25
Front to back ratio (dB)	22
Vertical electrical tilt (°)	0
Port Isolation (dB)	23

Ports

	Port 1	Port 2
Connector	SMA, jack (female)	SMA, jack (female)
Polarization	-45° slant	+45° slant
DC grounded	No	No

Connections

Band 1	
Port 1	X
Port 2	X

General Data

Mechanical Data

Dimensions (mm)	101 x 95 x 32 (Height x Width x Depth)
Weight (kg)	0.11
Windload	frontal: 15 N at 160 km/h , Wind speed survival: km/h
Mast diameter (mm)	40 - 60
Included mounting material	Wall mounting material

Mounting socket material: ASA
 Mounting socket colour: RAL 7042

Environmental Data

Environmental conditions indoor

SENCITY Planar WiFi Antenna 1356.19.0009

Operation temperature (°C)	-40 to 80
Storage temperature (°C)	-40 to 80
Transport temperature (°C)	-40 to 80
RoHS 2011/65/EU	compliant
Lead-free soldered	yes
REACH 2006/1907/EC	compliant

Material Data

Radome colour	RAL 7035 (light-grey)
Radome material	ASA (acrylic ester-styrene-acrylonitrile)
Back plate/base plate colour	RAL 7035 (light-grey)
Back plate/base plate material	Aluminium

Related Products

9091.99.0029 Pol Bracket
9091.99.0080 Sidetilt Bracket

Related Documents

Mounting instruction	DOC-0000197953
Painting instruction	DOC-0000256180
Security instruction	DOC-0000278984
Outline drawing	DOU-00019981.1

Additional Information