BME.1M.200.XAZ





Summary


Request a quote					
Catalog					
Size	1M				
Series	M - Rugged Ratchet coupling				

Technical details

Form & Material

Shell style / Model id	BME - Blanking cap for fixed receptacle(knurled grip)			
Housing material	Aluminium (nickel plated [SAE AMS QQ N 290], anthracite color) shell and nut, other pieces bronze/brass			
Keying	3 keys (alpha=42, gamma=30, plug: male contacts, receptacle: female contacts)			
Colour	Gray			
Weight	4.51 g			
Environment				
Technical domain	Motorsport, Security and Defence, Transportation, Aerospace and UAV			
Environmental sealing (IP rating)	IP68			
Temperature range	-55°C / +135°C			
EMI Shielding EIA 364-66A	>= 80 dB (1 GHz), >=70 dB (3 GHz), >= 58 dB (6 GHz), >= 40 dB (10 GHz)			
Gunfire vibration	25 Hz - 2000 Hz, 3 axis (Apache helicopter)			
Humidity (max)	21 days at 95%			
Lighting strike EIA 364-76	10K amps - 6 times			
Shock Resistance	300 g [3 ms]			
Thermal shock	5 cycles: -65°C to +150°C			
Vibration-Random	37.8 g rms - 3 axes, 4 hr amb [50 Hz - 2000 Hz]			
Vibration-Sine	30 g, 3 axes, 12 hr [10 Hz - 2000 Hz]			
Salt Spray Corrosion	max. 48 hr			

Drawings



Dimensions

	A	С	L	N	Р	X	
mm.	14.6	14.2	23.4	85	3.9	6	
in.	0.57	0.56	0.92	3.35	0.15	0.24	