

Part Number : 5023510900

Series Number : 502351 Product Category : Connector Housings

Documents & Resources

Drawings Drawing 5023510900_sd.pdf

3D Models and Design Files 3D Model 5023510900_stp.zip

Specifications

Packaging Specification PK-502351-001-001.pdf Product Specification PS-502351-002-001.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant
China RoHS	©
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Not Low-Halogen per IEC 61249-2- 21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

Product Description : DuraClik Wire-to-Board Receptacle Housing, Single Row, 9 Circuits, Natural Status : Active

- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Connector Housings
Series	502351
Description	DuraClik Wire-to-Board Receptacle Housing, Single Row, 9 Circuits, Natural
Application	Automotive, Signal, Wire-to-Board
Comments	Molex part has an inner-locking system versus an outer-locking system. Molex part with tail protection feature.
Product Family	DuraClik Connector System
Product Name	DuraClik
UPC	887191656984

Physical

Circuits (maximum)	9
Color - Resin	Natural
Gender	Receptacle
Glow-Wire Capable	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Net Weight	0.342/g
Number of Rows	1
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	2.00mm
Polarized to Mating Part	Yes
Temperature Range - Operating	-40° to +105°C

Mates with Part(s)

Description	Part Number
DuraClik Right-Angle Single Row Headers	502352
DuraClik Vertical Single Row Headers	560020

Use with Part(s)

Description	Part Number
Pre-Crimped Lead DuraClik Female- to-DuraClik Female, Tin (Sn) Plating, 150.00mm Length, 26 AWG, Black	/content/molex/molex-dot- com/us/en/products/product-page- pdf.html/797581008.html
Pre-Crimped Lead DuraClik Female- to-DuraClik Female, Tin (Sn) Plating, 300.00mm Length, 26 AWG, Black	/content/molex/molex-dot- com/us/en/products/product-page- pdf.html/797581009.html
DuraClik Female Crimp Terminals	560085
Micro-Latch Female Crimp Terminals	50212
DuraClik Female Terminals	<u>56161</u>

This document was generated on Sep 18, 2024