

Search Product:

[\[Advanced \]](#)

- ? [Adapters & power supplies](#)
- ? [Batteries & chargers](#)
- ? [Cables & accessories](#)
- ? [Connectors](#)
- ? [Consumer products & pc acc.](#)
- ? [Electronic components](#)
- ? [High-q tools & dmm's](#)
- ? [Led products & lamps](#)
- ? [Light products](#)
- ? [Loudspeakers & pa systems](#)
- ? [Perel tools](#)
- ? [Security products](#)
- ? [Velleman kits & oscilloscopes](#)

[ROHS Info](#)[HIGH - Q TOOLS & DMM'S](#) > [OSCILLOSCOPE PROBE SETS](#) >

INSULATED SCOPE PROBE 60MHz

Order Code: PROBE60S



Features

- ? complete probe set
- ? safety: conform with IEC-1010 cat II
- ? attenuation: 1:1 or 1:10

Specifications

- ? position x1:
 - ? attenuation: 1:1
 - ? bandwidth: DC to 15MHz
 - ? rise time: 23.3ns
 - ? input resistance: 1Mohm (input resistance scope)
 - ? input capacitance: 46pF + cap. scope
 - ? working voltage: 600V DC incl. peak AC derating with frequency
 - ? position REF:-
- ? position x10:
 - ? attenuation: 1:10
 - ? bandwidth: DC to 60MHz
 - ? rise time: 5.8ns
 - ? input resistance: 10Mohm (if scope input = 1Mohm)
 - ? input capacitance: ± 15pF
 - ? working voltage: 600V DC incl. peak AC derating with frequency
 - ? compensation range: 10 to 50pF
- ? cable length: 4ft
- ? remarks: with insulated BNC connector

Files

- ? [EN- FR- NL](#)

Stock Info

- ? Inner carton:
- ? Outer Carton: 100
- ? EAN Barcode: 5410329221980
- ? Packaging: Plastic Bag