

## Coaxial Cable Connector 25\_SMA-50-2-25/111\_N

### Description

Straight panel cable jack, flange mount

Interface standards

IEC 60169-15\_MIL-STD-348A/310\_CECC 22110



### Technical Data

#### Electrical Data

Impedance 50  $\Omega$   
Interface frequency max. 18 GHz

#### Mechanical Data

Centre contact soldered  
Outer contact soldered  
Weight 0.0019 kg

#### Environmental Data

Operating temperature -65 °C to 165 °C  
2011/65/EU, RoHS compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	

### Related Documents

Outline drawing DOU-00009024  
Catalogue drawing DCA-00009026  
Assembly instruction DOC-0000179086

### Ordering Information

Single package 25\_SMA-50-2-25/111\_NE

### Additional Information

Suitable cables EZ\_86\_TP\_M17, SUCOFORM\_86, MULTIFLEX\_86

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[25\\_SMA-50-2-25/111\\_NE](#)