

Product Description: GWconnect Screw Terminal Insert, Female, 10-Pole, 16A, with Wire Protection, Silver (Ag) Plated Contacts, Part Number: 936010231

Size 10B «57x27»

Series Number: 93601 Status: Active

**Product Category**: Heavy-Duty Connectors Engineering Number: 7310.6004.0

### **Product Environment Compliance**

### Compliance

| GADSL/IMDS         | Not Relevant                                       |
|--------------------|--|
| China RoHS         | <b>®</b>   |
| EU ELV             | Not Relevant                                       |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                     |
| REACH SVHC         | Contains Lead per D(2024)4144-DC<br>(27 June 2024) |
| EU RoHS            | Compliant per EU 2015/863                          |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

#### **Part Details**

#### General

| Status   | Active                |
|----------|-----------------------|
| Category | Heavy-Duty Connectors |
| Series   | 93601                 |

| Description    | GWconnect Screw Terminal Insert,<br>Female, 10-Pole, 16A, with Wire<br>Protection, Silver (Ag) Plated<br>Contacts, Size 10B «57x27» |
|----------------|---|
| Component Type | Inserts - Screw Terminal  |
| Insert Series  | S-E   |
| Product Family | GWconnect Heavy Duty Connectors (HDC)   |
| Product Name   | GWconnect   |
| Standard       | CSA C22.2 NO. 182.3, EN 60664-1,<br>EN 61984, UL 1977   |
| UPC            | 887191877891  |

# Agency

| CSA | 256883  |
|-----|---------|
| UL  | E249674 |

# Electrical

| Current - Maximum per Contact | 16.0A |
|-------------------------------|-------|
| Voltage - Maximum             | 500V  |
| Wire Protection               | Yes   |

# Physical

| Component Size                 | 10B «57X27»    |
|--------------------------------|----------------|
| Durability (mating cycles max) | 700            |
| Gender                         | Female         |
| Insert Color                   | Grey           |
| Material - Contact             | Copper Alloy   |
| Material - Insert              | Polycarbonate  |
| Material - Plating             | Silver         |
| Net Weight                     | 63.000/g       |
| Number of Rows                 | 2              |
| Packaging Type                 | Bag            |
| Polarized to Mating Part       | Yes            |
| Poles                          | 10             |
| Stripping Length               | 7.00mm         |
| Temperature Range - Operating  | -40° to +125°C |

| Tightening Test Torque    | 0.50 Nm   |
|---------------------------|-----------|
| Wire Size (AWG)           | 14-20     |
| Wire Size mm <sup>2</sup> | 0.50-2.50 |

### Mates With / Use With

## Mates with Part(s)

| Description   | Part Number      |
|---|------------------|
| GWconnect Screw Terminal Insert,<br>Male, 10-Pole, 16A, with Wire<br>Protection, Silver (Ag) Plated<br>Contacts, Size 10B «57x27» | <u>936010238</u> |

### Use with Part(s)

| Description | Part Number                            |
|-------------|--|
| Use With    | Size 10B «57x27» Hoods and<br>Housings |

This document was generated on Sep 18, 2024