




Connectors > Modular Jacks & Plugs > RJ45 Connectors



Modular Jack & Plug Interface Type: **RJ45**

Port Configuration: **Single Port**

Port Matrix Configuration: **1 x 1**

Modular Jacks & Plugs Products: **RJ Type Jacks & Plugs**

Connector Contact Density: **Standard**

Features

Product Type Features

| | |
|------------------------------------|-----------------------|
| Connector Product Type | Connector Assembly |
| Modular Jack & Plug Interface Type | RJ45 |
| Modular Jacks & Plugs Products | RJ Type Jacks & Plugs |
| Modular Connector Style | Jack |
| Grounding Options | PCB and Panel Ground |
| Connector & Contact Terminates To | Printed Circuit Board |

Configuration Features

| | |
|----------------------------|--------------|
| Panel Ground Location | Top and Side |
| Number of PCB Ground Tabs | 2 |
| Port Configuration | Single Port |
| Port Matrix Configuration | 1 x 1 |
| Connector Contact Density | Standard |
| Number of Positions | 8 |
| Number of Loaded Positions | 8 |
| PCB Mount Orientation | Right Angle |



Body Features

| | |
|--------------------------------|---------------------|
| LED Color (Top Left) | Green |
| LED Color (Top Right) | Yellow |
| Shield Plating Finish | Matte |
| Shield Plating Material | Tin |
| Shield Material | Copper Alloy |
| Modular Jack Latch Orientation | Inverted - Latch Up |
| Connector Profile | Standard |

Contact Features

| | |
|--|-----------------|
| PCB Contact Termination Area Plating Material Finish | Matte |
| Contact Underplating Material | Nickel |
| PCB Contact Termination Area Plating Material | Tin |
| Contact Current Rating (Max) | 1.5 A |
| Contact Mating Area Plating Material | Gold |
| Contact Base Material | Phosphor Bronze |
| Contact Mating Area Plating Material Thickness | 1.27 µm[50 µin] |

Termination Features

| | |
|--------------------------------|----------------|
| Termination Method to PCB | Surface Mount |
| Termination Post & Tail Length | .86 mm[.03 in] |

Mechanical Attachment

| | |
|--------------------------|-------------|
| Panel Mount Feature | With |
| PCB Mount Retention Type | Boardlock |
| Connector Mounting Type | Board Mount |

Housing Features

| | |
|-----------------------|------------------------------|
| Mating Entry Location | Side |
| Centerline (Pitch) | 1.02 mm[.04 in] |
| Housing Color | Black |
| Housing Material | LCP (Liquid Crystal Polymer) |

Dimensions

| | |
|-----------------------------|-------------------|
| PCB Thickness (Recommended) | 1.57 mm[.062 in] |
| Connector Height | 13.35 mm[.525 in] |

Usage Conditions



| | |
|-----------------------------|---------------------------|
| Operating Temperature Range | -40 – 85 °C[-40 – 185 °F] |
|-----------------------------|---------------------------|

Operation/Application

| | |
|---------------------|--------|
| Indicator Type | LED |
| Shielded | Yes |
| Circuit Application | Signal |

Industry Standards

| | |
|------------------------|----------|
| UL Flammability Rating | UL 94V-0 |
| Performance Category | Cat 5 |

Packaging Features

| | |
|--------------------|------|
| Packaging Quantity | 200 |
| Packaging Method | Reel |

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>


| | |
|---|---|
| EU RoHS Directive 2011/65/EU | Compliant |
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Reflow solder capable to 245°C |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>




Compatible Parts




TE Part # 188729-1
8P.COVER/SOLD.STOP


Customers Also Bought




TE Part #6-1879021-1
SMW3 33R 5%




TE Part #2-1761607-7
IDC LOW PRO HDR 20P RA LG LAT




TE Part #5-103904-4
5 MTE HDR SRRA LATCH W/HLDWN




TE Part #5-103908-4
05 MTE HDR SRST LATCH W/HLDWN




TE Part #3-794630-2
02P MICRO MNL ASSY,VRT,HDR,LF




TE Part #880584-1
SHUNT CONNECTOR



TE Part #2-2324245-4
ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5



TE Part #1759503-1
mini PCI-E 8H Type I PKG G/F



TE Part #1825027-1
FSMRA1JHL04=R/A,TACT PB SW,100

Documents

- CAD Files
- 3D PDF
- 3D
- Customer View Model
- ENG_CVM_CVM_6339191-4_D_c-6339191-4-d.2d_dxf.zip
- English
- Customer View Model



[ENG_CVM_CVM_6339191-4_D_c-6339191-4-d.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_6339191-4_D_c-6339191-4-d.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English