



**DB25F AND TRS WIRING CHART**

TRS (CHANNEL)	CABLE (COLOR)	TIP (RED)	RING (BLACK)	SLEEVE (BARE)
1	BROWN	24	12	25
2	RED	10	23	11
3	ORANGE	21	9	22
4	YELLOW	7	20	8
5	GREEN	18	6	19
6	BLUE	4	17	5
7	PURPLE	15	3	16
8	GRAY	1	14	2

**NOTES:**

- BREAKOUT CABLE LENGTH: 18 +/- 0.75 INCHES. SEE TABLE FOR COLOR.
- THIS PRODUCT COMES COILED AND PACKAGED IN BAG.
- MATERIALS:  
 TRS PLUG AND HANDLE - COPPER ALLOY, NICKEL PLATED  
 H.S. TUBING - THERMOPLASTIC  
 DSUB:  
 CABLE CLAMP - COPPER, NICKEL PLATED  
 SHELL - STEEL, TIN PLATED  
 INSULATORS - THERMOPLASTIC  
 SCREW LOCKS - COPPER ALLOY, NICKEL PLATED
- THIS PRODUCT IS RoHS COMPLIANT.

**CUSTOMER DRAWING**

REV	ECO NUMBER	DATE	BY	APVD
C	27520	06/08/15	PC	TJK
B	26637	10/4/10	RS	TJK
A	26568	7/20/10	RS	TJK

REVISIONS

UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS IN INCHES [mm]  
 - TWO PLACE DECIMALS ±0.02 [0.5]  
 - THREE PLACE DECIMALS ±0.005 [0.13]

**DO NOT SCALE DRAWING**

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.									
SIZE	WIDTH	MULT	LBS/M	TEMPER					
FINISH					MATERIAL				
SPEC No.					SPEC No.				
FIRST USED ON				SCALE 1:2					
DATE DRAWN	BY	CHKD	APVD	<b>Switchcraft</b> <sup>®</sup>					
7/16/09	JGK	RS	TJK						
NAME				PART No.					REV
DB25F TO 8-TRS, RoHS				DB25FTRS					C