

Product data sheet

Miniature connectors



Product description **M16 Male panel mount connector, Contacts: 5 (05-a), unshielded, single wires, IP67, UL**


Area **series 723**

Part no. **09 0115 702 05**


Illustration



Scale drawing



Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

Technical data

General features

Part no.	09 0115 702 05
Connector design	Male panel mount connector
Type standard	DIN EN 61076-2-106
Version	Connector pin straight
Connector locking system	screw
Termination	single wires
Degree of protection	IP67
Cross-sectional area	AWG 22
Temperature range from/to	-30 °C / 85 °C
Mechanical operation	> 500 Mating cycles
Weight (g)	17.21
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	300 V
Rated impulse voltage	1500 V
Rated current	5.0 A
Insulation resistance	$\geq 10^{10} \Omega$
Pollution degree	1
Insulating material group	II
EMC compliance	unshielded

Material

Housing material	Zinc die-cast nickel-plated
------------------	-----------------------------

Product data sheet

Miniature connectors



Product description **M16 Male panel mount connector, Contacts: 5 (05-a), unshielded, single wires, IP67, UL**

Area **series 723**
Part no. **09 0115 702 05**

Contact body material	PBT (UL94 V-0)
Contact material	CuSn (bronze)
Contact plating	Ag (silver)
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	547601b0-c303-4ed5-b9c7-2f14e3761ae5

Authorization/approvals

Approvals	UL
-----------	----


Classifications

ETIM 9.0	EC003569
----------	----------

Product data sheet
Miniature connectors

Product description	M16 Male panel mount connector, Contacts: 5 (05-a), unshielded, single wires, IP67, UL
Area	series 723
Part no.	09 0115 702 05

Assembly instructions / Panel cut-out



Product description	M16 Male panel mount connector, Contacts: 5 (05-a), unshielded, single wires, IP67, UL
Area	series 723
Part no.	09 0115 702 05

Security notices

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

The plug connector is not suitable for mains voltages. Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 60 cNm).