



Circuit Diagram

PCB Layout (Pattern side) [®]

NO.1			
PART NO	H	L	F
A	4.3	3.30	∅3.40
C	5	4.00	∅3.40
D	5.5	4.50	∅3.40
E	6	5.00	∅3.40
F	6.5	5.50	∅3.30
G	7	6.00	∅3.30
H	7.5	6.50	∅3.30
I	8	7.00	∅3.20
J	8.5	7.50	∅3.20
K	9	8.00	∅3.20
L	9.5	8.50	∅3.20

NO.2	
PART NO	vigor
1	90±30
2	130±30
3	180±30
4	250±30
5	350±50

NO.3	
PART NO	MATERIAL/QTY
S	SUS/1PC
C	C5210/1PC
D	SUS/2PCS
F	C5210/2PCS

NO.4-NO.5	
PART NO	NOTE
01~99	SERIAL NUMBER

⑥	Trestle	—	1	SPCC	Plating Nickel	—
⑤	Terminal	—	2	Brass(0.30t)	Plating silver	—
④	Contact	—	1	F.Ag/SUS	Plating silver	—
③	Base	—	1	Nylon	Black	—
②	Cover	—	1	SPCC	Plating Nickel	—
①	Keystoke	—	1	Nylon	Black	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS		DATE	HRO 華榮 [®] ELECTRONICS CO.,LTD			
DRAWN	J.X.Zhang	2013/5/30	TITLE:	TACT SWITCHES		
CHECKED			PART NO.	K2-1102BG-□□□W-□□		
APPROVALS			UNIT: mm	SCALE: 1:1	PROJ:	
TOLERANCES ARE	30~以上: ±0.30	ANGLE	DRAWING NO.		SHEET 1 OF 1	
	10~30: ±0.20					
	5~10: ±0.15	±2'				
	~ 5: ±0.10					

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			