ROHS











P.C.B Layout (copper-sided view)

Rating:0.5A 30V DC
Contact Resistance:100 mΩ Max.
Operating temperature:-20℃~70℃
Operating force:3-20N
Operating Life:5,000cycles

Model NO	PJ-384-A	PJ-384-B
Schematic		

ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK
②	Terminal	——	3	Phosphor bronze	Au Plating	——
①	Housing	——	1	Nylon	Black	——

APPROVALS		DATE	HRO韩荣® ELECTRONICS CO.,LTD		
DRAWN	J.X.Zhang	2013/11/11			
CHECKED			TITLE:	PHONE JACKES	
APPROVALS			PART NO.	PJ-384	
TOLERANCES ARE	30~以上 ±0.30 / 10~30 ±0.20 / 5~10 ±0.15 / ~5 ±0.10	ANGLE ±2°	UNIT: mm	SCALE: 1:1	PROJ:
			DRAWING NO.	——	SHEET 1 OF 1

ECN NO.	REV.	DATE.	DESCRIPTION.	DRAWN	CHECK.	APPRO.
——	B	——	增加视图和PIN脚定义图	2016.10.18	——	——
——	A	——	NEW	——	——	——