



Specifications:

规格:

Voltage rating: 250V AC/DC
 额定电压: 250V AC/DC
 Current rating: 1A AC/DC
 额定电流: 1A AC/DC
 Withstanding voltage: 500V AC/minute
 耐受电压: 500V AC/分钟
 Temperature range: -40°C-+105°C
 温度范围: -40°C-+105°C
 Insulation resistance: 1000MΩ min
 绝缘电阻: 1000MΩ Min
 Contact resistance: 20mΩ Max
 接触电阻: 20mΩ Max

X2001 HA2 -2xXX- PT V01
 ① ② ③ ④ ⑤

1. Series No
2. Category: HA2-Three piece double contact
3. Row No. Pin No: 2xXX-2x03P-2x30P
4. Material: PT-PBT Glass Fiber UL94V-0
5. Plating: V01-Gold Flash

Poles	Dimensions		Poles	Dimensions	
	A	B		A	B
2x03	11.20	4.00	2x13	31.20	24.00
2x04	13.20	6.00	2x14	33.20	26.00
2x05	15.20	8.00	2x15	35.20	28.00
2x06	17.20	10.00	2x17	39.20	32.00
2x07	19.20	12.00	2x18	41.20	34.00
2x08	21.20	14.00	2x20	45.20	38.00
2x09	23.20	16.00	2x22	49.20	42.00
2x10	25.20	18.00	2x25	55.20	48.00
2x11	27.20	20.00	2x30	65.20	58.00
2x12	29.20	22.00		/	

X2001HA2-2xXX-PTV01	PBT Glass Fiber	Brass	X2001W
PART NO	Material	Material(Pin)	Suitable XKB Wafer

广东星坤科技股份有限公司
 文件工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
ANGLAR				±5°
L ≤ 4				±0.2
4 < L ≤ 16				±0.3
16 < L ≤ 63				±0.4
L > 63				±0.5

XKB	DSND	SCALE: N/A	MODEL TYPE:
	DWN	VIEW:	2.0mm IDC Connector
	CHKD	UNIT: mm/in	PART NO.:
	APPD	SIZE: A4	X2001HA2-2xXX-PTV01
			DWG NO.:
			X-X2001HA2-2xXX-PTV01
XKB INDUSTRIAL PRECISION CO., LIMITED		WEIGHT	SHEET
		1/1	REVISION
			A0