



Specifications:

规格:
 Voltage rating: 250V AC/DC
 额定电压: 250V AC/DC
 Current rating: 1A AC/DC
 额定电流: 1A AC/DC
 Withstanding voltage: 500V AC/minute
 耐受电压: 500V AC/分钟
 Temperature range: -40°C~+105°C
 温度范围: -40°C~+105°C
 Insulation resistance: 1000MΩ min
 绝缘电阻: 1000MΩ Min
 Contact resistance: 20mΩ Max
 接触电阻: 20mΩ Max

X2001 W R - 2xXX D - 6T V01
 ① ② ③ ④ ⑤ ⑥ ⑦

- Series No
- Category: W-Wafer
- Welding Board Angle: R-Stright 90°
- Row No. Pin No.: 2xXX-2x03-2x30P
- Category: D-Short ears
- Material: 6T-Nylon 6T UL94V-0
- Plating: V01-Gold Flash

Poles	Dimensions		Poles	Dimensions	
	A	B		A	B
2x03	4.00	21.60	2x13	24.00	41.60
2x04	6.00	23.60	2x15	28.00	45.60
2x05	8.00	25.60	2x17	32.00	49.60
2x06	10.00	27.60	2x20	38.00	55.60
2x07	12.00	29.60	2x22	42.00	59.60
2x08	14.00	31.60	2x25	48.00	65.60
2x10	18.00	35.60	2x30	58.00	75.60
2x12	22.00	39.60	/		

X2001WR-2xXXD-6TV01	Nylon 6T	Brass	X2001H
PART NO	Material	Material(Pin)	Suitable XKB IDC

DSND	SCALE: N/A	MODEL TYPE: 2.0mm Crimp Style Connector
DWN	VIEW:	PART NO.: X2001WR-2xXXD-6TV01
CHKD	UNIT: mm/in	DWG NO.: X-X2001WR-2xXXD-6TV01
APPD	SIZE: A4	WEIGHT
XKB INDUSTRIAL PRECISION CO., LIMITED		SHEET
		REVISION
		1/1
		A0



ANGULAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5
UNSPECIFIED TOLERANCES	

广东星坤科技股份有限公司

DATE	DESCRIPTION
DATE	DESCRIPTION
DATE	DESCRIPTION

文件工程章