

## Dual P-channel Enhancement Mode Power MOSFET


### Features

- $V_{DS} = -30V$ ,  $I_D = -5A$   
 $R_{DS(ON)} < 37m\Omega$  @  $V_{GS} = -10V$   
 $R_{DS(ON)} < 52m\Omega$  @  $V_{GS} = -4.5V$


### General Features

- Advanced Trench Technology
- Provide Excellent  $R_{DS(ON)}$  and Low Gate Charge
- Lead Free and Green Available


100% UIS TESTED!  
100%  $\Delta V_{ds}$  TESTED!



SOP-8 (Dual)



Pin Assignment



Schematic diagram

### Absolute Maximum Ratings $T_C = 25^\circ C$ , unless otherwise noted

| Parameter                                        | Symbol         | Value      | Unit       |
|--------------------------------------------------|----------------|------------|------------|
| Drain-Source Voltage                             | $V_{DS}$       | -30        | V          |
| Continuous Drain Current                         | $I_D$          | -5         | A          |
| Pulsed Drain Current (note1)                     | $I_{DM}$       | -20        | A          |
| Gate-Source Voltage                              | $V_{GS}$       | $\pm 20$   | V          |
| Power Dissipation                                | $P_D$          | 1.6        | W          |
| Single pulse avalanche energy (note2)            | $E_{AS}$       | 12         | mJ         |
| Operating Junction and Storage Temperature Range | $T_J, T_{stg}$ | -55 To 150 | $^\circ C$ |

### Thermal Resistance


| Parameter                               | Symbol     | Value | Unit         |
|-----------------------------------------|------------|-------|--------------|
| Thermal Resistance, Junction-to-Ambient | $R_{thJA}$ | 78    | $^\circ C/W$ |

| Specifications T <sub>J</sub> = 25°C, unless otherwise noted |                      |                                                                            |       |      |      |      |
|--------------------------------------------------------------|----------------------|----------------------------------------------------------------------------|-------|------|------|------|
| Parameter                                                    | Symbol               | Test Conditions                                                            | Value |      |      | Unit |
|                                                              |                      |                                                                            | Min.  | Typ. | Max. |      |
| Static Parameters                                            |                      |                                                                            |       |      |      |      |
| Drain-Source Breakdown Voltage                               | V <sub>(BR)DSS</sub> | V <sub>GS</sub> = 0V, I <sub>D</sub> = -250μA                              | -30   | --   | --   | V    |
| Zero Gate Voltage Drain Current                              | I <sub>DSS</sub>     | V <sub>DS</sub> = -30V, V <sub>GS</sub> = 0V                               | --    | --   | -1   | μA   |
| Gate-Source Leakage                                          | I <sub>GSS</sub>     | V <sub>GS</sub> = ±20V                                                     | --    | --   | ±100 | nA   |
| Gate-Source Threshold Voltage                                | V <sub>GS(th)</sub>  | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = -250μA                | -1    |      | -3   | V    |
| Drain-Source On-Resistance                                   | R <sub>DS(on)</sub>  | V <sub>GS</sub> = -10V, I <sub>D</sub> = -5A                               | --    |      | 37   | mΩ   |
|                                                              |                      | V <sub>GS</sub> = -4.5V, I <sub>D</sub> = -4A                              | --    |      | 52   |      |
| Forward Transconductance                                     | g <sub>FS</sub>      | V <sub>DS</sub> = -5V, I <sub>b</sub> = -5A                                | --    | 6.2  | --   | S    |
| Dynamic Parameters                                           |                      |                                                                            |       |      |      |      |
| Input Capacitance                                            | C <sub>iss</sub>     | V <sub>GS</sub> = 0V,<br>V <sub>DS</sub> = -15V,<br>f = 1.0MHz             | --    | 592  | --   | pF   |
| Output Capacitance                                           | C <sub>oss</sub>     |                                                                            | --    | 76   | --   |      |
| Reverse Transfer Capacitance                                 | C <sub>rss</sub>     |                                                                            | --    | 66   | --   |      |
| Total Gate Charge                                            | Q <sub>g</sub>       | V <sub>DD</sub> = -15V,<br>I <sub>D</sub> = -5A,<br>V <sub>GS</sub> = -10V | --    | 11   | --   | nC   |
| Gate-Source Charge                                           | Q <sub>gs</sub>      |                                                                            | --    | 2    | --   |      |
| Gate-Drain Charge                                            | Q <sub>gd</sub>      |                                                                            | --    | 3    | --   |      |
| Turn-on Delay Time                                           | t <sub>d(on)</sub>   | V <sub>DD</sub> = -15V,<br>I <sub>D</sub> = -5A,<br>R <sub>G</sub> = 3Ω    | --    | 13   | --   | ns   |
| Turn-on Rise Time                                            | t <sub>r</sub>       |                                                                            | --    | 7    | --   |      |
| Turn-off Delay Time                                          | t <sub>d(off)</sub>  |                                                                            | --    | 14   | --   |      |
| Turn-off Fall Time                                           | t <sub>f</sub>       |                                                                            | --    | 9    | --   |      |
| Drain-Source Body Diode Characteristics                      |                      |                                                                            |       |      |      |      |
| Continuous Body Diode Current                                | I <sub>S</sub>       | T <sub>C</sub> = 25°C                                                      | --    | --   | -5   | A    |
| Body Diode Voltage                                           | V <sub>SD</sub>      | T <sub>J</sub> = 25°C, I <sub>SD</sub> = -5A, V <sub>GS</sub> = 0V         | --    | --   | -1.2 | V    |
| Reverse Recovery Charge                                      | Q <sub>rr</sub>      | I <sub>F</sub> = -5A, V <sub>GS</sub> = 0V<br>di/dt=-100A/us               | --    | 5.3  | --   | nC   |
| Reverse Recovery Time                                        | T <sub>rr</sub>      |                                                                            | --    | 11   | --   | ns   |


## Notes

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2. EAS condition :  $T_J = 25^{\circ}\text{C}$ ,  $V_{DD} = -30V$ ,  $V_{GS} = -10V$ ,  $L = 0.5mH$ ,  $R_G = 25\Omega$
3. Identical low side and high side switch with identical  $R_G$


Gate Charge Test Circuit



Switch Time Test Circuit



EAS Test Circuit



Typical Characteristics  $T_J = 25^\circ\text{C}$ , unless otherwise noted

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Drain Source On Resistance




Figure 4. Gate Charge




Figure 5. Capacitance






Figure 6. Source-Drain Diode Forward




**Typical Characteristics**  $T_J = 25^\circ\text{C}$ , unless otherwise noted

**Figure 7. Drain-Source On-Resistance**



**Figure 10. Safe Operation Area**



**Figure 9. Normalized Maximum Transient Thermal Impedance**

