


SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 125V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltage: 500V AC/minute
- 7、Material: PA66, UL94V-0

编 号	尺寸 (mm)	
	A	B
A1002-02Y	1.00	3.00
A1002-03Y	2.00	4.00
A1002-04Y	3.00	5.00
A1002-05Y	4.00	6.00
A1002-06Y	5.00	7.00
A1002-07Y	6.00	8.00
A1002-08Y	7.00	9.00
A1002-09Y	8.00	10.00
A1002-10Y	9.00	11.00
A1002-11Y	10.00	12.00
A1002-12Y	11.00	13.00
A1002-20Y	19.00	21.00



单位 UNIT	mm
比例 SCALE	1:1
核准: APPROVED BY	.x±.x
审核: CHECKED BY	.xx±.xx
制图: DRAWN BY	.xxx±0.005, .xxx±.xxx

泰华电子有限公司

TaiHua Electronics Co., Ltd

版本: VERSION	A0	产品名称 Product name	1.0超薄孔座
页次: PAGE	1/1	产品料号 Product No	TH-A1002-NY
日期: DATE	2022.8.31	客户料号 Client No	