


PCB LAYOUT

- SPECIFICATIONS
- 1、Current Rating: 1A AC, DC
  - 2、Voltage Rating: 125V AC, DC
  - 3、Temperature Range: -25°C~+85°C
  - 4、Contact Resistance: 20mΩ Max
  - 5、Insulation Resistance: 100mΩ Min
  - 6、Withstanding Voltage: 500V AC/minute
  - 7、Material: Wafer Nylon46, UL94V-0  
PIN Phosphoric copper Tin-plated  
Solder tads Phosphoric copper Tin-plated

编 号	尺寸 (mm)	
	A	B
A1251WF-02A	1.25	7.35
A1251WF-03A	2.50	8.60
A1251WF-04A	3.75	9.85
A1251WF-05A	5.00	11.10
A1251WF-06A	6.25	12.35
A1251WF-07A	7.50	13.60
A1251WF-08A	8.75	14.85
A1251WF-09A	10.00	16.10
A1251WF-10A	11.25	17.35
A1251WF-11A	12.50	18.60
A1251WF-12A	13.75	19.85
A1251WF-15A	17.50	23.60



单位  
UNIT

深圳市泰华电子有限公司  
**TaiHua Electronics Co., Ltd**

比例  
SCALE

版本: A0  
产品名称: 1.25引脚插座

核准:  
APPROVED BY

图次: 1/1  
产品编号: TH-A1251WF-NA

审核:  
CHECKED BY

日期:  
客户编号: (Client No)

.XXX±0.005, XXX±

封文编号: 2022.8.31

