


PCB LAYOUT

- SPECIFICATIONS
- 1、Current Rating: 4A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 1000MΩ Min
 - 6、Withstanding Voltage: 1000V AC/minute
 - 7、Material: Wafer Nylon66, UL94V-0
PIN Brass Tin-plated

编号	尺寸 (mm)	
	A	B
A2542-02A	2.54	5.08
A2542-03A	5.08	7.62
A2542-04A	7.62	10.16
A2542-05A	10.16	12.70
A2542-06A	12.70	15.24
A2542-07A	15.24	17.78
A2542-08A	17.78	20.32
A2542-09A	20.32	22.86
A2542-10A	22.86	25.40
A2542-11A	25.40	27.94
A2542-12A	27.94	30.48
A2542-20A	48.26	50.80



单位	mm
X ₁ ±0.5	X ₁ ±0.5
X ₂ ±0.30	X ₂ ±0.3
X ₃ ±0.20	X ₃ ±0.2
.xxx±0.005	.xxx±0.005

深圳市泰华电子有限公司
TaiHua Electronics Co., Ltd

核准:	版本:	产品名称	2510直针 WAFER DIP TYPE
APPROVED BY	A0	Production name	
审核:	页次:	产品编号	TH-A2542-NA
CHECKED BY	1/1	Product No	
制图:	日期:	客户编号	
DRAWN BY	2022.9.1	Client No	

版本	变更日期	变更理由
1.0	2022.9.1	首版