



SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltage: 1000V AC/minute
- 7、Material: Nylon66, UL94V-0

编 号	尺寸 (mm)	
	A	B
A2506-02Y	2.50	7.40
A2506-03Y	5.00	9.90
A2506-04Y	7.50	12.40
A2506-05Y	10.00	14.90
A2506-06Y	12.50	17.40
A2506-07Y	15.00	19.90
A2506-08Y	17.50	22.40
A2506-09Y	20.00	24.90
A2506-10Y	22.50	27.40
A2506-11Y	25.00	29.90
A2506-12Y	27.50	32.40
A2506-20Y	47.50	52.40

	单位 UNIT	mm	<p style="text-align: center;">泰华电子有限公司 <i>TaiHua Electronics Co., Ltd</i></p>	
$x \pm 0.5$	x:±			
$x \pm 0.30$.x:±			
$.xx \pm 0.20$.xx:±			
$.xxx \pm 0.005, xxx \pm$.xxx:±		版本: A0	产品名称 Production name
	标准: APPROVED BY		页次: 1/1	5294孔座
	审核: CHECKED BY		日期:	产品料号 Product No
	制图: DRAWN BY	封文馨 2022.3.1		TH-A2506-NV
				客户料号 Client No

版本 REV	变更事项 CHANGE CONTENT	日期 THRENUMBER	变更日期 DATE
A0			