



SPECIFICATIONS

- 1、Current Rating: 15A AC, DC
- 2、Voltage Rating: 600V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Min
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltage: 5000V AC/minute
- 7、Material: Nylon66, UL94V-0

编 号	尺寸 (mm)		
	A	B	C
C6350-02P	6.35	14.20	23.10
C6350-03P	12.70	20.55	29.50
C6350-04P	19.05	26.90	35.80
C6350-05P	25.40	33.25	42.15
C6350-06P	31.75	39.60	48.50
C6350-08P	44.45	52.30	61.20



X. ±0.5	X*±
. X±0.30	. X*±
. XX±0.20	. XX*±
. XXX±0.005, XXX*±	

深圳市泰华电子有限公司  
**TaiHua Electronics Co., Ltd**

单位 UNIT	mm	版本: A0	产品名称 Production name	63080单排孔座
比例 SCALE		审核: APPROVED BY	产品料号 Product No	TH-C6350-NP
		复核: CHECKED BY	客户料号 Client No	
		制图: DRAWN BY	日期: DATE	
			2023.01.31	

版本 REV	变更日期 CHANGE DATE	变更内容 CHANGE CONTENT
A0		