


PCB LAYOUT

编号	尺寸 (mm)	
	A	B
C6350-02A	6.35	14.20
C6350-03A	12.70	20.55
C6350-04A	19.05	26.90
C6350-05A	25.40	33.25
C6350-06A	31.75	39.60
C6350-08A	44.45	52.30

SPECIFICATIONS

- 1、Current Rating: 15A AC, DC
- 2、Voltage Rating: 600V AC, DC
- 3、Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 4、Contact Resistance: $20\text{m}\Omega$ Max
- 5、Insulation Resistance: $1000\text{M}\Omega$ Min
- 6、Withstanding Voltage: 5000V AC/minute
- 7、Material: Wafer Nylon66, UL94V-0
PIN Brass Tin-plated



单位 UNIT mm
比例 SCALE

X. ±0.5 X* ±
. X ±0.30 X* ±

. XX ±0.20 . XX* ±

. XXX ±0.005 . XXX* ±

批准: APPROVED BY	版本: A0	产品名称: 63080单排直针 WAFER DIP TYPE
审核: CHECKED BY	页次: 1/1	产品料号: TH-C6350-NA
制图: DRAWN BY	日期: 2023.01.31	客户料号: Client No

深圳市泰华电子有限公司
TaiHua Electronics Co., Ltd

版本: A0	客户料号: CLIENT NO	生产日期: DATE
--------	-----------------	------------