



PCB LAYOUT

- SPECIFICATIONS**
- 1、Current Rating: 2A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 1000MΩ Min
 - 6、Withstanding Voltage: 1000V AC/minute
 - 7、Material: Wafer LCP, UL94V-0
PIN Brass Tin-plated
Solder Phosphoric bronze Tin-plated

编号	尺寸 (mm)	
	A	B
A2006LF-02A	2.00	8.00
A2006LF-03A	4.00	10.00
A2006LF-04A	6.00	12.00
A2006LF-05A	8.00	14.00
A2006LF-06A	10.00	16.00
A2006LF-07A	12.00	18.00
A2006LF-08A	14.00	20.00
A2006LF-09A	16.00	22.00
A2006LF-10A	18.00	24.00
A2006LF-11A	20.00	26.00
A2006LF-12A	22.00	28.00
A2006LF-20A	38.00	44.00

		单位 UNIT	mm
X ±0.5 X ±0.30 .XX ±0.20 .XXX ±0.005, XXX ±		比例 SCALE	
核准: APPROVED BY		版本: A0	产品名称 Production name
审核: CHECKED BY		页次: 1/1	产品料号 Product No
制图: DRAWN BY		日期: 2022.9.5	客户料号 Client No
封文辉 2022.9.5		泰华电子有限公司 TaiHua Electronics Co., Ltd HY立贴 WAFER SMT TYPE TH-A2006LF-NA	

版本 REV	变更事项 CHANGE CONTENT	依据 REFERENCE	变更日期 DATE
NO			