



- SPECIFICATIONS**
- 1、Current Rating: 3A AC, DC
 - 2、Voltage Rating: 250V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 1000MΩ Min
 - 6、Withstanding Voltage: 800V AC/minute
 - 7、Material: Nylon66, UL94V-0

编 号	尺寸 (mm)	
	A	B
B2513-02Y	2.50	5.80
B2513-03Y	5.00	8.30
B2513-04Y	7.50	10.80
B2513-05Y	10.00	13.30
B2513-06Y	12.50	15.80
B2513-07Y	15.00	18.30
B2513-08Y	17.50	20.80
B2513-09Y	20.00	23.30
B2513-10Y	22.50	25.80
B2513-11Y	25.00	28.30
B2513-12Y	27.50	30.80
B2513-20Y	47.50	50.80

PCB LAYOUT

	单位 UNIT	mm	泰华电子有限公司 TaiHua Electronics Co., Ltd
	比例 SCALE		
x.±0.5	x.±		版本: A0
.x±0.30	.x.±		批准: APPROVED BY
.xx±0.20	.xx.±		审核: CHECKED BY
.xxx±0.005, xxx.±	.xxx.±		制图: DRAWN BY 2022.3.5
			日期: DATE
			客户料号: Client No
			产品名称: Product name
			产品料号: Product No
			生产单号: Production name
			页次: 1/1
			TH-B2513-NV
			JC2513底座

版本 REV	变更事项 CHANGE CONTENT	日期 DATE
1.0		
1.1		
1.2		
1.3		
1.4		
1.5		
1.6		
1.7		
1.8		
1.9		
2.0		