



- SPECIFICATIONS**
- 1、Current Rating: 3A AC, DC
  - 2、Voltage Rating: 250V AC, DC
  - 3、Temperature Range: -25°C~+85°C
  - 4、Contact Resistance: 20mΩ Max
  - 5、Insulation Resistance: 1000MΩ Min
  - 6、Withstanding Voltage: 800V AC/minute
  - 7、Material: Wafer PBT, UL94V-0  
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A2026-02AW	2.00	6.00
A2026-03AW	4.00	8.00
A2026-04AW	6.00	10.00
A2026-05AW	8.00	12.00
A2026-06AW	10.00	14.00
A2026-07AW	12.00	16.00
A2026-08AW	14.00	18.00
A2026-09AW	16.00	20.00
A2026-10AW	18.00	22.00
A2026-11AW	20.00	24.00
A2026-12AW	22.00	26.00

深圳市泰华电子有限公司  
TaiHua Electronics Co., Ltd

	单位 UNIT	mm
$x.\pm 0.5$	比例 SCALE	
$x.\pm 0.30$	版本: APPROVED BY	A0
$x.\pm 0.20$	审核: CHECKED BY	1/1
$.xxx\pm 0.009, .xxx\pm$	制图: DRAWN BY	封文辉 2023.01.31
	日期:	
	客户料号 Client No	
	产品名称 Production name	PA定位弯针
	产品料号 Product No	TH-A2026-NAWD