


PCB LAYOUT

编 号	尺寸 (mm)		
	A	B	C
A3961-02AB	3.96	9.90	11.88
A3961-03AB	7.92	13.86	15.84
A3961-04AB	11.88	17.82	19.80
A3961-05AB	15.84	21.78	23.76
A3961-06AB	19.80	25.74	27.72
A3961-07AB	23.76	29.70	31.68
A3961-08AB	27.72	33.66	35.64
A3961-09AB	31.68	37.62	39.60
A3961-10AB	35.64	41.58	43.56
A3961-11AB	39.60	45.54	47.52
A3961-12AB	43.56	49.50	51.48

SPECIFICATIONS

- 1、Current Rating: 7A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperatuér Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltage: 1500V AC/minute
- 7、Material: Wafer LCP, UL94V-0
PIN Brass Tin-plated



X. ±0.5	X*±
. X±0.30	. X*±
. XX±0.20	. XX*±
. XXX±0.005, .XXX*±	

深圳市泰华电子有限公司
TaiHua Electronics Co., Ltd

单位 UNIT	mm	版本: A0	产品名称 Production name	VH WAFER SMT TYPE
比例 SCALE		核准: APPROVED BY		
		审核: CHECKED BY	产品料号 Product No	TH-A3961-NAB
		制图: DRAWN BY	日期: Date	
			封文辉 2022.10.24	
			客户料号 Client No	

版本 REV	变更日期 CHANGE DATE	变更描述 CHANGE DESCRIPTION
1.0		